

Aluminium Louver Doors & Window IUCAI-AALM Product Range

Serial Number	Numbering	Name	Features	Schematic
1	IX2TLC80	80Two-track non-breaking bridge sash	<ol style="list-style-type: none"> 1. The use of high water retaining edge, sash interior, easy installation. 2. Upper and lower rails with wide-track design, double pulley, sliding doors and windows to run smoothly. 3. Profile section superior mechanical properties, high wind pressure strength. 4. High window, good economy. 5. Optional fan yarn ordinary nylon gauze and stainless steel steel mesh. 6. Broken bridge material and non-bridge material to choose from. 	
2	IX3TLC90	90Three-track non-breaking bridge sash	<ol style="list-style-type: none"> 1. The use of high water retaining edge, sash interior, easy installation. 2. Upper and lower rails with wide-track design, double pulley, sliding doors and windows to run smoothly. 3. Profile section superior mechanical properties, high wind pressure strength. 4. Can be equipped with stainless steel steel mesh. 	

3	IG1PKC55	55Broken bridge energy-saving windows	<p>1. Mining profiles for the broken bridge, thermal insulation, sound insulation superior performance.</p> <p>2. Adopt double-channel sealed insulating glass, air-tightness, watertightness, excellent sound insulation.</p> <p>3. High-quality stainless steel hinges or standard European hinge.</p> <p>4. Can be made into indoor and outdoor two-colour windows of different colours, to achieve the purpose of the window colour and indoor and outdoor environment.</p>	
4	IX1PKC65	65Non-broken bridge windows	<p>1. Profile for the bridge of this design, mechanical properties to meet the requirements of different environments.</p> <p>2. Adopt double-channel sealed insulating glass, air-tightness, watertightness, excellent sound insulation.</p> <p>3. Continental hinge or invisible stainless steel hinges to meet the installation requirements of different customers for easy removal and installation.</p> <p>4. Gauze fans made of stainless steel mesh, two-point lock, with anti-mosquito and security features.</p>	

5	IG1PKC85	85Broken bridge energy-saving windows	<p>1. When there are high winds the style greatly reduces the risk of people suffering from the cold because the style disperses the wind flow.</p> <p>2. The use of nylon PA66, insulation, heat insulation, sound insulation, set the advantages of insulation materials in one bridge.</p> <p>3. Continental hinge or stainless steel hinges can be used to open, to meet the installation requirements of different customers.</p> <p>4. Can be made into indoor and outdoor two-colour windows of different colours, to achieve the purpose of the window colour and indoor and outdoor environment.</p>	
6	IG1PKC100	100Broken bridge energy-saving windows	<p>1. Frame width of 100mm, gives a rich, stylish and safe look.</p> <p>2. The use of nylon PA66, insulation, heat insulation, sound insulation, set the advantages of insulation materials in one bridge.</p> <p>3. Continental hinge or stainless steel hinges can be used to open, to meet the installation requirements of different customers.</p> <p>4. Can be made into indoor and outdoor two-colour windows of different colours, to achieve the purpose of the window colour and indoor and outdoor environment.</p> <p>5. Optional security security grid, the user has security features.</p>	

7	IG1PKC110	110Broken bridge energy-saving windows	<p>1. The use of nylon PA66, insulation, heat insulation, sound insulation, set the advantages of insulation materials in one bridge.</p> <p>2. Continental hinge or stainless steel hinges can be used to open, to meet the installation requirements of different customers.</p> <p>3. Can be made into indoor and outdoor colour windows of different colours, to achieve the purpose of the window colour and indoor and outdoor environment coordination.</p> <p>4. Gauze fans made of stainless steel gauze, multi-point lock, with anti-mosquito and security features.</p> <p>5. Optional security security grid, with security features.</p> <p>6. Glass optional magnetic or electronic built-in louver, is conducive to adjusting lighting, blocking direct sunlight, and more suitable for office space.</p>	
8	IX1TSC801	80Non-broken bridge single pull window	<p>1. Airtightness, watertightness and sound insulation that can not be compared with the traditional way of opening.</p> <p>2. With the use of screens, can play a pest control, dust-proof effect.</p> <p>3. Open does not take up interior space, flexible, easy to clean.</p>	
9	IX1TSC802	80Non-bridge double pull window		

10	IX1TLSC2	Anti-theft two push screens	<p>1.Product Features: Mosquito control, pest control, tampering, anti-theft, anti-fall, corrosion-resistant.</p>	
11	IX1TLSC3	Three anti-theft push window	<p>2.Features: High-performance two-way locking system, built-in spring switch, more beautiful and safer, more convenient to use, save space.</p> <p>3.Applicable window type: outside the window, hanging window.</p>	
12	IX1PKSM35	Anti-theft 35 flat open screen door	<p>1.Mosquito control, pest control, corrosion resistance</p> <p>2.Anti-theft strength, to prevent damage or snakes, rats, flies, mosquitoes and other animals invasion.</p> <p>3.Prevention of fall objects, can effectively protect the elderly living room and children playing.</p> <p>4.The interior is always bright and natural, easy to open and easy to escape.</p>	
13	IX1KDJM46	46KFC door	<p>1.Widely used in offices, restaurants, shopping malls, channels and other crowded places.</p> <p>2.Beautiful shape, simple lines, close structure.</p> <p>3.Can be opened inside or outside, open up to 180 degrees.</p> <p>4.Frame fan line pressure line, there are different slot pressure line to choose from, you can install single glass or insulating glass.</p> <p>5.Accessories optional world axis or floor spring.</p>	

14	IX2ZXTM14	1.4 two-track non-breaking bridge sliding door	<p>1. Widely used in senior clubs, kitchen, living room, bedroom, home gardens and other space compartment.</p> <p>2. Profile with European standard metal notch, double hook lock body to connect multiple lock points, but also enhance security, theft tampering.</p> <p>3. Door with anti-swing anti-shake device, stainless steel under the rail, so that the process of sliding light, no noise, no shaking.</p>	
15	IX3ZXTM14	1.4 three-track non-breaking bridge sliding door	<p>4. Dual EPDM sealant strip, the use of pressure balance principle to achieve wet and dry seal.</p> <p>5. There are two tracks, three track and package edge line for selection.</p>	
16	IX2ZXTM20	2.0 two-track non-breaking bridge sliding door	<p>1. Widely used in luxury villas, senior clubs, large hotels, home gardens and other space compartment.</p> <p>2. Imported hardware accessories, compact structure, flexible operation, without shaking, super wind pressure and shock resistance.</p> <p>3. Double decorative effect, the look from the indoor warm and elegant, with the look luxurious from the outside, improves the quality of buildings.</p>	
17	IX3ZXTM20	2.0 three-track non-breaking bridge sliding door	<p>4. Optional hollow shutter system to enhance the sliding system.</p> <p>5. There are two tracks, three track and package edge line for selection.</p>	

18	IX1YGF140	140 sun room	<p>1.Outdoor recreation building the best choice!</p> <p>2.With unique design and function, to home, office decoration brings a new visual enjoyment and comfort experience.</p> <p>3.Compact structure, reasonable stress, the overall strength, with the broken bridge windows, sliding doors, swing doors and other matching.</p> <p>4.Simple and generous, to meet different architectural styles of matching the needs of the roof shape.</p>	
19	IX1LBS99	99 aluminium villas	<p>1.The use of aluminium alloy manufactured for Villa products.</p> <p>2.Low cost, short construction period, quick investment, strong earthquake resistance and pollution-free, which is compliant to the theme of energy saving and environmental protection which is foreseen as a bright future for the Villa industry.</p> <p>3.Has good wind resistance, durability, thermal insulation, fire resistance and many other advantages.</p>	